



Thermal Receipt Printer


LW-RP-TM-T20i

- Multiple interface connections, auto-cutter, wall mountable.
- Support both 58mm and 80mm width paper. (300mm speed support)
- Queuing function, re-printing function. (USB+Lan, USB+Serial+Lan)
- IAP online upgrade, printer head over-temperature protection function, and cutter anti-jam function
- Support a variety of 1D barcode and 2D barcode printing.
- Compatible with ESC/POS commands.
- Support Windows, Linux, Android, IOS, OPOS, and MacOS



LW-RP-TM-T20i

Thermal Receipt Printer



Model	LW-RP-TM-T20i
Printing method	Direct thermal
Printing speed	260 mm/s
Paper width	80mm
Column capacity	576 dots/line or 512 dots/line
Interface	USB+Serial+Lan
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Simplified/Traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Simplified/Traditional Chinese: 3.0×3.0mm (24×24 dots)

Barcode Character	
Extension character sheet	PC347 (Standard Europe) / Katakana / PC850 (Multilingual) / PC860 (Portugal) / PC863 (Canadian) / PC865 (Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866 (Cyrillic#2) / PC852 (Latin2) / PC858 / IranII / Latvian / Arabic / PT151 (1251)
1D Barcode	UPC-A/UPC-E/JAN13 (EAN13)/JAN8 (EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE
Input buffer	USB / USB+Serial: 96 Kbytes USB+Lan : 256 Kbytes
NV Flash	256 Kbytes

Power	
Power adaptor	Input: AC 100~240V, 50~60Hz
Printer Input	DC 24V/2.5A
Cash drawer	DC 24V/1A

Physical characteristics	
Weight	1.0 Kg
Dimensions	194.5*145*146.4mm

Environmental Requirements	
Work environment	Temperature (0~45℃) humidity (10~80%)
Storage environment	Temperature (-10~60℃) humidity (10~90%)

Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150Km

Software	
Emulation	ESC/POS
Driver	Windows/JPOS/Linux/OPOS/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS, Android, Windows

