

| LIGHTWAVE-lightwaveglobal |                              |                                  |                           |
|---------------------------|------------------------------|----------------------------------|---------------------------|
| TECHNICAL DATA SHEET      |                              |                                  |                           |
| MODEL                     |                              | LW-SF-1655R                      | LW-SF-1666R               |
| SPECIFICATION             |                              |                                  |                           |
| POWER RATING VA           |                              | 50W                              | 50W                       |
| INPUT                     | VOLTAGE RANGE                | 220-240V                         | 220-240V                  |
|                           | FREQUENCY                    | 50Hz                             | 50Hz                      |
| OUTPUT                    | VOLTAGE(INVERTER MODE)       | N/A                              | N/A                       |
|                           | CAPACITY                     | N/A                              | N/A                       |
|                           | FREQUENCY(INVERTER MODE)     | N/A                              | N/A                       |
|                           | TRANSFER TIME                | N/A                              | N/A                       |
|                           | WAVEFORM OVER/UNDER VOLT.    | N/A                              | N/A                       |
| PROTECTION                | SPIKE AND SURGE SUPPRESSION  | N/A                              | N/A                       |
|                           | OVER/UNDER VOLTAGE           | N/A                              | N/A                       |
|                           | OVER LOAD / SHORT CIRCUIT    | 145°C non-resettable fuse        | 145°C non-resettable fuse |
| BATTERY                   | TYPE                         | N/A                              | N/A                       |
|                           | RECHARGE TIME                | N/A                              | N/A                       |
|                           | BACKUP TIME (DEPEND ON LOAD) | N/A                              | N/A                       |
| PHYSICAL                  | WEIGHT(KGS)                  | 6.4KG                            | 6.4KG                     |
|                           | SHIPPING WEIGHT(KGS)         | 7.25KG                           | 7.25KG                    |
|                           | DIMENSION(MM)                | 510*135*570mm                    | 510*135*570mm             |
| EFFICIENCY                | AC-AC                        | Yes                              | Yes                       |
|                           | DC-AC                        | No                               | No                        |
| ACOUSTIC                  | NOISE LEVEL                  | Not test                         | Not test                  |
| ENVIRONMENTAL             | TEMPERATURE                  | Depends on the usage environment |                           |
|                           | HUMIDITY                     |                                  |                           |
| POWER OUTLETS             | NO. AND TYPES                | two round pin plug               | two round pin plug        |