

LIGHTWAVE - UNINTERRUPTED POWER SUPPLY

Technical Data Sheet

Model		LW UPS 1500VA
Specification		
Power Rating VA		1500VA
Input	Voltage Range	145Vac ~ 280Vac
	Frequency	50Hz / 60Hz +/- 10%
Output	Voltage (Inverter Mode)	230v +/- 10%
	Capacity	1500VA / 900W
	Frequency (Inverter Mode)	50Hz / 60 Hz +/- 10%
	Transfer Time	<10ms
	Waveform Over/Under Volt.	Modified Sinewave
Protection	Spike and Surge Suppression	YES
	Over / Under Voltage	Switch to Battery Mode, When main's voltage exceeds range
	Over Load / Short Circuit	Fuse & Current limited for both mains and battery modes
Battery	Type	Lead-Acid Maintenance Free Battery
	Recharge Time	8 Hrs > 90%
	Backup Time (Depend on Load)	5 to 15 Mins
Physical	Weight (Kgs)	10
	Shipping Weight (Kgs)	11
	Dimension (mm)	325 x 145 x 220
Efficiency	AC - AC	1
	DC - AC	0.6
Acoustic	Noice Level	< 45 dB
Environmental	Temperature	- 5 ⁰ C to 45 ⁰ C
	Humidity	20 to 90 %
Power Outlets	No. and Types	3 Sockets / Universal